- 2. (Amended) The floor covering as claimed in Claim 1, wherein the polyolefin has a density of 0.85 0.892 g/cm<sup>3</sup>.
- 3. (Twice Amended) The floor covering as claimed in Claim 1, wherein the polyolefin is selected from among the class of VLD PE polymers.
- 4. (Twice Amended) The floor covering as claimed in Claim 1, wherein the polyolefin is a mixture of at least two ethylene copolymers, wherein the ethylene copolymer mixture comprises a copolymer (a) as the main polymer with a density of 0.89 0.91 g/cm<sup>3</sup> and a copolymer (b) to control rheology and elasticity with a density of 0.86-0.88 g/cm<sup>3</sup> and an MFI > 3.
- 5. (Amended) The floor covering as claimed in Claim 4, wherein the copolymers (a) and (b) are present at a weight ratio of 4:1 to 3:2.

(Twice Amended) The floor covering as claimed in Claim 4, wherein the

- copolymers (a) and (b) are copolymers of ethylene and octene.
- 7. (Twice Amended) The floor covering as claimed in Claim 1, wherein the grafted copolymer is a grafted copolymer based on a HD polyethylene.

6.



- 8. (Amended) The floor covering as claimed in Claim 7, wherein the grafted copolymer is a maleic acid anhydride grafted HD polyethylene.
- 9. (Amended) The floor covering as claimed in Claim 8, wherein the grafting degree is 1% to 5%.
- 10. (Twice Amended) The floor covering as claimed in Claim 1, wherein the proportion of grafted copolymer in relation to the total weight of the polymeric binder is 5% to 25% by weight.
- 11. (Twice Amended) The floor covering as claimed in Claim 1, wherein the elastomer is cross-linked with at least one cross-linking agent based on an organic peroxide and optionally a co-cross-linking agent.



12. (Amended) The floor covering as claimed in Claim 11, wherein the co-cross-linking agent is an isocyanuric acid derivative or an acrylate or a methacrylate derivative derived from a polyol.



13. (Twice Amended) The floor covering as claimed in Claim 1, which further comprises a filler, a pigment, a processing aid, an antioxidant, a static eliminator, a UV stabilizer or a slip agent.